

HORTUSS® EXCLUSIVE OUTDOOR FLOORING

PROFESSIONALS



WHAT'S PRATI GROUP ?

THE GROUP

Prati Group S.p.A. (Reggio Emilia - Italy)

The Group has a total turnover of 22 million Euros. Prati Spa Group mainly operates in the italian market with 45 employees and 30 representatives. Floover World SL operates exclusively on international markets with 15 employees and 10 representatives

ITALY

Lithos (Reggio Emilia - Italy)

Lithos produces and sells on the italian market floating floorings with click system, splitted in 4 product lines: laminate floorings, engineered wood floorings, high design floorings (pvc, real leather, cork, real stone, linoleum, etc.), outdoor floorings.



Hortus International (Reggio Emilia - Italy)

Hortus produces and sells on the international markets outdoor floorings with the brand Hortus (In Italy the Hortus brand is included in the Lithos range)



Floover World SL (Barcelona - Spain)

WORLDWIDE



Company based in Barcelona that produces and sells on the international markets LVT, real leather, cork, rubber and real stone floorings. In the Spanish headquarter are developed business strategies and planning. It is the control center for finance, supervision, personnel, technology, product development, distribution and communication.

> Floover Switzeland (Mustair - Svitzerland)



Companies based in Switzerland that is specialized in the production and in the logistics service of the Floover products.





PRATI GROUP VALUES

PROFESSIONALISM

Company, employees and consultants are required to perform all operations with diligence and professionalism. Everyone is required to provide an adequate working contribution to the role and responsibilities assigned by contract, acting in order to ensure high quality standards in services offered as well as to protect the reputation and integrity of Prati Group S.p.A.



FAIRNESS AND TRANSPARENCY

Interpersonal relationship among all employees and the company and among the company's staff and customers and suppliers, must be loyalty, transparency and mutual respect.

PP Prati spa

CHART OF VALUES

RISPECT AND OBSERVANCE 3 **OF INTERNAL OPERATING** PROCEDURES

Company, employees and consultants comply to compliance and enforcement of Company Rules and safety standards provided by law.



WITH LAWS AND REGULATIONS

Company, employees and consultants share as essential principle the respect of national and local laws.

Company, employees and consultants ensure the respect of applicable directives and the compliance of specific tasks related to the activities carried out and compliance with the contractual specifications agreed with customers and suppliers.



HORTUS® EXCLUSIVE OUTDOOR FLOORING

WHAT'S HORTUS?

HORTUS PRODUCTION

Hortus is the best choice for outdoor spaces: the elegance, the inimitable naturalness and warmth of natural wood are combined with creativity, originality and innovation arising from the exclusive Hortus Woven project

 Hortus floorings are available in 2 versions:
wood with the essence Thermo Ash
woven (woven pvc glued on a polystirene strip base)

The sizes are: 300 x 300 e 300 x 600 mm

The Hortus factory has a production capacity of 600.000 units per year on a 1 daily shift of 8 hours

The Hortus product with the thermo ash essence is FSC certified: the management system of the chain of custody provided by Prati Group complies with the standard FSC-STD-40-004 Version 2.1

Prati Group is a company ISO 9001 certified



Covering of woven strips phase









HORTUS® EXCLUSIVE OUTDOOR FLOORING

VERSIONS









DESTINATIONS OF USE



... in wellness center

A product functional and hygienic for use in saunas, fitness centers, spas and beachside areas.



... around the swimming pool

Thanks to its features Hortus floorings are perfect also for swimming pool decks, beach side areas and spas, where complete safety when walking barefoot is an essential requirement.





... on the terrace

A versatile and modular solution that is perfectly suited to any type of furniture (both modern and classic) and allows the designer to vary the compositions obtaining floorings in line with the new trends of design and style

DESTINATIONS OF USE



... in restaurant

The resistance to external agents, to slipping and impacts make Hortus ideal for paving outdoor restaurants also non-permanent enhancing colors and shapes with the constant respect of the surroundings.



... in the courtyard ... in the garden

A practical and convenient solution that harmonizes perfectly with the natural surroundings and makes it the ideal furnishing accessory: in the paths, in the gazebos, on terraces and gardens.





... on the wall

An unusual and distinctive covering on the external wall of houses, offices, hotels and shops. Hortus can be a warm and natural solution with wood collection or innovative and unique solution with woven collection



HORTUS® EXCLUSIVE OUTDOOR FLOORING

WOOD LINE

HORTUS WOOD ADVANTAGES

• EASY TO INSTALL: JUST A CLICK! REMOVABLE EXTREME VERSATILITY AND FLEXIBILITY OF USE AESTHETIC VALUE RESPECT FOR THE ENVIRONMENT LONG-LASTING RESISTANT TO PATHOGENS EASY MAINTENANCE WITH OIL SELECTED RAW MATERIALS



WOOD SPECIES



TEAK

- Colour: from golden brown to tobacco brown
- Density: 0,58 0,70 g/cm³
- Shrinkage: low
- Swelling: low
- Hardness: medium
- Dimensional stability: high
- Durability (unassailable from moulds, germs and pathogens): very high



IPE'

- Colour: greenish brown with yellowish and reddish reflections
- Density: 0,85 1,10 g/cm³
- Shrinkage: medium/high
- Hardness: very high
- Dimensional stability: medium
- Durability (unassailable from moulds, germs and pathogens): high
- Swelling: medium/high





THERMOTREATED ASH

- Colour: from warm brown colour to dark brown
- Density : 0,55 0,65 g/cm³
- Shrinkage : medio/low
- Hardness: medium/high
- Dimensional stability medium/high
- Durability : very high
- Swelling : medium/low

ASH THERMO TREATMENT

- Hortus floor for outdoor is made of European Ash coming from FSC certified forests.
- The heat treatment allows to obtain excellent results of durability of the wood over time, preventing the germination of mushrooms and moulds, without the use of nouns and chemical and preservatives substances.
- □ With heat treatment, the cellular structure of wood changes permanently. The wood is, in fact, subjected to temperatures of about 200 °, under controlled humidity and atmospheric oxygen depletion.
- The intensity and duration of heat causing an accelerated aging of ligneous materials, resulting in an apparent color change of tone besides to a higher hardness and strength of the product.
- Heat is also able to alter irreversibly and permanently alter the molecular structure of the wood resulting in a gradient of swelling and withdrawal reduced.
- This particular heat treatment ensures dimensional stability far superior to those of untreated wood and helps them also to increase the strength similar to that determined by the natural aging of wood.
- □ The result of this heat treatment is a general darkening and homogeneous color tone. The various hues are obtained by treatment of different duration: more we prolong the heating process, darker will be the wood.
- □ With heat treatment, in addition, the splitting of the natural sugars present in the wood, gives a more uniform color and protects against mould and Xylophagia.
- □ The heat-treated products may also be considered as an ecological alternative to tropical woods: you can have a nice warm brown without having cleared the rainforest.
- □ Last but not less important, unlike the stained wood, the floors heat-treated can be sanded many times without ever losing their colour as the colour is also present within the wood due to heat treatment.



HORTUS ASH IS FSC CERTIFICATED



II marchio della gestione forestale responsabile

CHOOSING FSC CERTIFIED HORTUS PRODUCTS, YOU MAKE A RESPONSIBLE CHOICE, ACTIVELY CONTRIBUTING TO THE PROTECT AND THE IMPROVEMENT OF THE WORLD WOOD AND FOREST HERITAGE

THE STRENGHTS OF STANDARD FSC:

- The FSC label, identifies products which contain wood from forest managed in responsible manner and according to strict environmental, social and aconomic standars.
- The forest of origin was monitored and evaluated independently, in compliance with these standards (principles and criteria of goods forest management), established and approved by the Forest Stewardship Council a.c. through participation and consent of parts involved.
- The cutting of trees is done with care, and even after cutting the logs are processed carefully. This approach helps to minimize the impacts on the ecosystem and prevent social conflict.
- The FSC standard also requires that the "chain of custody" is certified, or that it is always possible to trace the forest of origin to a certain part of timber, even when this is combined with other consignments from non-certified forests, in the many steps that lead from the forest to the store.
- FSC certification ensures environmentally sustainable exploitation of forests, with no cuts and no illegal exploitation of workers engaged in the production cycle, from cutting the trees to the finished product.



WOOD LINE SIZES





FSC www.fsc.org 100% Legno da foreste correttamente gestite FSC® C030501



300 x 300



wood essence

(thickness 17 mm)

Easy-fit, removable wood flooring, consisting of wood tiles impregnated with water-based oil, total thickness 32 mm, made by fixing, with zinc-coated screws, 4 wood strips to a draining plastic base



polypropylene grid base

INTERLOCKING SYSTEM



zinc coated screw with double thread

polypropylene grid base



RANGE 300 x 300 TILE

WOOD SPECIES AND FINISHING CHART - smooth line







HORTUS® EXCLUSIVE OUTDOOR FLOORING

300 x 600 TILE



Easy-fit, removable wood flooring, consisting of wood tiles impregnated with water-based oil, total thickness 32 mm, made by fixing, with zinc-coated screws, 4 wood strips to a draining plastic base

> polypropylene grid base

Wood essence (thickness 17 mm) 4 planks (588 x 70 x 17 mm)

INTERLOCKING SYSTEM



zinc coated screw with double thread



Polypropylene grid base

RANGE 300 x 600 TILE

WOOD SPECIES AND FINISHING CHART - smooth line




WOOD SPECIES AND FINISHING CHART – striped line





HORTUS WOOD PICTURES





DECKING PUZZLE 1200

Easy-fit, removable wood flooring, supplied without oil treatment, with a total thickness of 37 mm; the wood strips are mounted on draining, removable plastic bases which are clicked together during installation.

Wood essence (thickness 21 mm)



polypropylene Puzzle grid base (sold separately)

5 polypropylene grids set for Decking Puzzle (sold separately)



Polypropylene Puzzle grid base

Plank (1200 x 95 x 21)



DECKING PUZZLE 1200

WOOD SPECIES AND FINISHING CHART - smooth line



FSC[®] C030501

ASH

WOOD SPECIES AND FINISHING CHART – striped line



FSC* C030501





DECKING PUZZLE PICTURES

112



WOVEN LINE

The first outdoor flooring with unique and unusual design

HORTUS WOVEN ADVANTAGES

WIDE VARIETY OF DECORS (B EXTREME VERSATILITY AND FLEXIBILITY OF USE (B **GIVES THE OPPORTUNITY TO CUSTOMIZE THE** (F **OUTDOOR SPACES ACCORDING TO YOUR OWN TASTE** WITHOUT ANY CARE AND MAINTENANCE **HEAT RESISTANT** (F UV RAY RESISTANT I00% RECYCLABLE **WATERPROOF IT DOESN'T ROT** (B) **CRUSHPROOF** (B) LONG LASTING (F) **RESISTANT TO PATHOGENS**





300 x 300



polystyrene plank

100 % reciclable

(thickness 16 mm)

Easy-fit and removable flooring, consisting of polystyrene tiles covered with a woven pvc sheet, with a total thickness of 31 mm, made by fixing, with zinc-coated screws, 4 polystirene strips to a draining plastic base

polypropylene grid base

INTERLOCKING SYSTEM




zinc coated screw with double thread

polypropylene grid base

woven pvc with fiberglass



NEW HORTUS WOVEN DECORS









Easy-fit and removable flooring, consisting of polystyrene tiles covered with a woven pvc sheet, with a total thickness of 31 mm, made by fixing, with zinc-coated screws, 4 polystirene strips to a draining plastic base

polystyrene plank 100 % reciclable (thickness 16 mm)



polypropylene grid base



zinc coated screw with double thread

polypropylene grid base

woven pvc with fiberglass



NEW HORTUS WOVEN DECORS

TURQUOISE SPICE STREAKED RED TRANQUILLITY **DEEP RED** STREAKED WHITE OCHRE REFLECTION **BOLD BEIGE** VIOLET





HORTUS® EXCLUSIVE OUTDOOR FLOORING

WOVEN DECKING

WOVEN DECKING

Polystyrene strips covered with a woven pvc sheet, with a total thickness of 46 mm (30 + 16 mm), to install on autoclave-treated supports pine beams mounted directly on the substrate. The flooring is made by interposing these strips, with the lenght of 234 cm, installed using stainless steel grids screwed on the beam

Dimensions of the strip: 2.340 (lenght) x 70 (width) x 16 (thickness) mm Dimensions of the beam: 2.000 (lenght) x 60 (width) x 30 (thickness) mm

40 mm

A4 colored stainless steel screw with conical head and reduced diameter

ASSEMBLY SYSTEM



polystyrene plank 100 % reciclable (thickness 16 mm)

> colored stainless steel screw



Autoclave-treated pine support beam


Accessories for 1 m²:

- 4 m. of beam
- Approx. 60 screws

You can choose the distance between a strip and the other one (from 0 mm)

woven pvc with fiberglass


WOVEN DECKING DECORS





WOVEN DECKING ACCESSORIES

SCREWS COLOR VARIATIONS



LEVELING RUBBER PAD

It compensates for irregularities in the height of the substrate up to 30 mm



Example

Available dimensions: 60 x 60 x 2/3/5/10 mm


INSERT HOLDER WITH LIMIT SWITCH

It adjusts the screwing depth





Available Thicknesses: 5/6/7/8 mm











HORTUS WOVEN PICTURES





HORTUS WOVEN PICTURES







HORTUS®

EXCLUSIVE OUTDOOR FLOORING

PACKAGING

PACKAGING





HORTUS® EXCLUSIVE OUTDOOR FLOORING

SAMPLE CASE

SAMPLE CASE



 HORTUS WOVEN TILE RANGE
HORTUS WOOD TILE RANGE





DISPLAY SYSTEM

SLIDE DISPLAY FOR HORTUS



SIZES INCLUDED: 300 x 300 TILE and 300 x 600 TILE

WOOD ESSENCES: THERMO ASH and IPE'

LAYOUT: 5 TILES on the vertical wall and 10 TILES on the inclined floor



SLIDE DISPLAY FOR HORTUS WOVEN



SIZES INCLUDED: 300 x 300 TILE and 300 x 600 TILE

WOVEN DECORS: at your own choice

LAYOUT: 5 TILES on the vertical wall and 10 TILES on the inclined floor





HORTUSS® EXCLUSIVE OUTDOOR FLOORING